



M Series 1000 Ice Cube Machine

Model: MD1000A-251B MY1000A-251B

MD1000W-251B
MY1000W-251B

☐ MD1000N-251B ☐ MY1000N-251B



M1000 Ice Machine on A570V Bin

- Up to 445 kgs (981 lbs) daily ice production and only 30.00" (76.00 cm) wide
- R-410A CFC-free refrigerant
- Easy access to food zone with removal of two screws and lift-off door
- White plastics in the food zone help identify areas needing cleaning
- Water shield, distribution tube, pump, floats, and trough removable by hand
- Available CleanAir[™] pack controls the growth of bacteria and fungi that form slime and cause odors in the food zone

Specifications

BTU Per Hour:

16,250 (average), 18,600 (peak)

Compressor:

Nominal Rating: 2 HP

Refrigerant:

R-410A

Operating Limits:

- Ambient Temperature Range: 1.7°C to 43.3°C
- Water Temperature Range: 1.7°C to 32.2°C
- Water Pressure Ice Maker Water In: Min. 20 psi (137.9kPA) Max. 80 psi (551.1kPA)

Machine warranty Beautiful Evaporating plate Solve Farts and labor Machine Warranty Compressor Solve So

Ice Machine Electric

220-240/50/1 standard

Total Circuit Ampacity:

Air Cooled: 13.8A Water Cooled: 13.1A Remote Cooled: 14.1A

Maximum Fuse Size:

20A

HACR-type circult breakers can be used

in place of fuses

Cube Size Available



Half-dice 3/8" x 11/8" x 7/8" (0.95 x 2.86 x 2.22 cm)



Dice 7/8" X 7/8" X 7/8" 2.22 X 2.22 X 2.22 (cm)





^O™ani̇̃towoc



M1000 on A570V Storage Bin

- A Electrical Entrance (2) Options
- B 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
- © 1/2" (1.27 cm) F.P.T. Ice Making Water Drain
- D 1/2" (1.27 cm) Auxillary Base Drain Socket
- E 3/4" (1.91 cm) Bin Drain
- F 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units) G 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units)

Installation Note - Minimum installation clearance: Top/sides: 8" (20.32 cm), back: 5" (12.70 cm).

Space-Saving Designs

M1000 A570V 79.50" Height 201.9cm 30.00" Width 76.20 cm 34.00" Depth 86.56 cm 430 lbsBin Storage 195 kg

Height includes adjustable bin legs 6.00" to 7.00" (15.24 cm to 17.78 cm) set at 6.00" (15.24 cm).

| Model | Ice Shape | Ice Production 24 Hours | | Power Usage kWh/100 lbs. | Water Usage 100 lbs. |
|--------------|---------------|-------------------------|--------------------|-----------------------------|-------------------------|
| | | 70°Air/ 50°F Water | 90°Air/ 70°F Water | @90°Air/70°F | 45.4 kgs. of Ice |
| MD1000A-251B | dice | 437 kg | 374 kg | 5.76 | 75.7 |
| | | 963 lbs | 825 lbs | | |
| MY1000A-251B | half-dice | 445 kg | 381 kg | 5.76 | 75.7 |
| | | 981 lbs | 839 lbs | | |
| MD1000W-251B | dice | 428 kg | 366 kg | 4.56 | 72.5 |
| | | 943 lbs | 806 lbs | | |
| MY1000W-251B | half-dice | 436 kg | 373 kg | 4.56 | 72.5 |
| | | 960 lbs | 822 lbs | | |
| MD1000N-251B | dice (iii) | 427 kg | 371 kg | 5.03 | 74.2 |
| | | 941 lbs | 818 lbs | | |
| MY1000N-251B | half-dice | 435 kg | 378 kg | 5.03 | 74.2 |
| | | 959 lbs | 833 lbs | | |

Order ice storage bin separately. Suffix of model "A" means air cooled condenser, Suffix of model "W" means water cooled condenser.

CleanAir[™] Pack Slime Inhibitor



Clean Air $^{\text{TM}}$ Pack Accessory is patented technology that releases chlorine dioxide on a controlled basis to inhibit the growth of bacteria and fungi that form slime and cause odors in the food zone ice machines.

Easy Access to Parts of Water System



Water shield, distribution tube, pump, floats, and trough removable by hand

Easy Access to Air Filter



Easy to clean, reusable air filter protects condenser from lint, grease and dust.

