



UNIVERSAL BARRIER-FREE VERSACOOLER® II WITH HANDS-FREE VERSAFILLER®

Energy and Water Conservation Technology PG8SBFSLY

Suggested Specification

Model PG8SBFSLY delivers 8.0 gph of 50° F degree water at 90° F ambient and 90° F inlet water. Model PGSBFSLY is a non-refrigerated drinking fountain and delivers ambient water. Both include the VersaFiller Sports Bottle Filler with hands free activation; units have four antimicrobial copper push pads to activate the manual flow of water for the cooler. Hands-free VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discoloration, odors and degradation. Basin is designed to eliminate splashing and standing water. Water saver "flexible guard" bubbler reduces waste water by 50% and operate between 20 and 100 PSI. Cabinet finish comes in sandstone on galvanized steel or brushed stainless steel. Use R-134a refrigerant. Complies with ANSI 117.1 and ADA. Listed by Underwriters Laboratories to US and Canadian standards. Complies with ANSI/NSF 61 and NSF/ANSI 372.

Models

- PG8SBFSLY delivers 8.0 gallons of chilled drinking water per hour.
- PGSBFSLY is a non-refrigerated fountain.

Standard Features

- Universal design allows universal installation
- Built-in 100 micron strainer stops particles before they enter the waterway.
- Waterways are Lead-Free in materials & construction
- Antimicrobial, flexible & one-piece water saver bubbler guard to protect against injury (polyester elastomer)
- Stainless steel top and heavy duty galvanized steel frame
- High efficiency cooling system and refrigerant R-134a
- Four antimicrobial copper push pads
- External stream height adjustment on lower unit
- Hand free VersaFiller
- Built in filter monitor and bottle counter

Finishes

- Standard cabinet finish: Sandstone powder coated paint on galvanized steel
- Optional finishes (at additional cost): Stainless steel and optional greystone powder coated paint



Installation

- Prior to roughing consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation.

Options (at additional cost)

- One piece chrome plated brass bubbler (036700-001)
- Flow switch for fountain (038035-001)
- VersaFilter

Limited 5-Year Warranty

(Continental limits of the United States and Canada)
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Antimicrobial Copper - EPA Registration No. 89187-3
- Oasis International Electric Water Coolers are listed by Underwriters Laboratories Inc. and comply with both U.S. and Canadian Requirements.
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.
- This unit complies with ARI standard 1010 Testing, Operating and Rating requirements (electric water coolers only).
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed.



Model	50° F Drinking Water 90° F Ambient Air Temp			Hot'N Cold Model	220-240Volts, 50-60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx
	Rated Capacity Liters/Hour	Base Rate Lites/Hour	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
PG8SBFSLY	60	30	No	No	1/4	2.2	457	No	Yes	100 Lbs
PGSBFSLY	Fountain Only							No	Yes	66 Lbs

Specifications subject to change without notice